

OPTIGRÜN SM/KG 20

Vegetation Mat

Optigrün Vegetation Mat pre-cultivated with sedum on a rotproof plastic carrier.



Material	rotproof coconut fabric carrier with substrate layer and pre-cultivated sedum vegetation
Thickness	approx. 15 - 25 mm
Tensile strength	approx. 5.0 kN/m
Coverage rate	90 % - 100 %
Weight when saturated	ca. 15.0 - 30.0 kg/m ²
Composition	about 10 sedum species and varieties
Delivery form	Rolled mats, standard dimensions 1.0 x 1.5 m on disposable pallet 1.2 x 1.2 m, special sizes on request. On request, on 50 mm PE core for crane laying
Quantity/delivered unit	according to size of order up to 40 m ² /disposable pallet

Area of use

- On pitched roof up to max. 45° roof pitch with anti-slip substructure
- With min. 70 mm layer height in areas at risk of wind suction

Special features

Remove transport packaging immediately on delivery and lay on prepared substrate. Unrolled mats will keep for 1-2 weeks at the most with sufficient irrigation and exposure to daylight.

The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigrün's technical knowledge at the time of publication. Optigrün reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.

Optigrün international AG

Am Birkenstock 15 – 19,
72505 Krauchenwies-Göggingen
Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East
Welwyn Garden City (Herts), AL7 1HL
Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk

